


-Steps have non-skif / anti-slip surface.  
 -The side ropes of the pilot ladder consist of two uncovered ropes not less than 20mm in diameter on each side and should be continuous at the bottom, with no joints and have a breaking strength of at least 24 KN per side rope.  
 -A permanent marking is provided at regular intervals (e.g. 1 meter, white black splitting distance pieces) throughout the length of the ladder consistent with ladder design, use and maintenance in order to facilitate the rigging of the ladder to the required height.

|  |                    |   |                |
|--|--------------------|---|----------------|
| Producer : WORLD CLEAN INTERNATIONAL S.A.  |                    | Material: HARDWOOD                                    |                |
| Title: PILOT LADDER 18 MTR   |                    | Approval: MEDB000001G ISO799-1(2019) Res. A. 1045(27) |                |
|  |                    | Components: 48 STEPS 3 SPREADERS 4 RUBBER STEPS       |                |
| <br><b>PILOT LADDERS</b><br>Manufacture:<br>WCI Pilot Ladders Panama Republic of Panama<br>Distributed for main ports in America | Weight: 185 kg     |   | Scale:         |
|  | Date: January 2021 |   | Size: "8.5x11" |
|  |                    |   | Units: mm      |
|  |                    | Rev. c.   | Page 1/1       |