

WHELEED 135L FOAM FIRE EXTINGUISHER

- Model: HY -F135
- Capacity : 135L
- Body Diameter : 406mm
- Overall Height : 1420mm
- Width : 530 mm
- Depth : 640 mm
- Type : Pressure storage type
- Fire Rating : A ☒ B
- Approx discharge time : >120s
- Working temp.range : 0☒ -+60☒
- Extinguish agent : AFFF Foam
- Working pressure : 12Bar (Working pressure 20 ☒)
- Test pressure : 27bar
- Burst pressure : 48.6Bar
- Manufactured&Certified to :
- EN 1866 -1 : 2007 ; EN 1866 -2:2014
- Approval : MED



WHEELED 45L FOAM FIRE EXTINGUISHER

- Model: HY -F45
- Capacity : 45L
- CO2 Cartridge :1.25kg
- Body Diameter : 300mm
- Overall Height : 1160mm
- Width : 450mm
- Depth : 500mm
- Fire Rating : A B
- Approx discharge time : 88s
- Working temp.range : 0^o -+60^o
- Extinguish agent : AFFF Foam
- Working pressure : 12Bar (Working pressure 20)
- Test pressure : 27bar
- Burst pressure : 48.6Bar
- Manufactured&Certified to : EN 1866 -1 : 2007 ; EN 1866 -2:2014
- Approval : MED



PORTABLE 12KG DRY POWDER FIRE EXTINGUISHER

- Model: HY -P12
- Capacity : 12kg
- Cylinder diameter : 184mm
- Overall height : 640mm
- Type : Pressure storage type
- Fire rating : 55A 233B C
- Approx discharge time : 32s
- Working temperature range : -30℃ - +60℃
- Extinguish agent : ABC Dry powder
- Working pressure : 14Bar at 20℃
- Test pressure : 27bar
- Burst pressure : ≥55Bar
- Manufactured&Certified to : BS EN 3 -7: 2004 + A1: 2007, BS EN 3 -8: 2021 and
BS EN 3 -10: 2009
- Approx full weight : 18.28 kg
- Approval : MED



PORTABLE 9L WATER FIRE EXTINGUISHER

- Model: HY -W9C
- Capacity : 9L
- CO2 Gas cartridge : 60g
- Cylinder diameter : 184mm
- Overall height : 590mm
- Type : Cartridge operated type
- Fire rating : 21A
- Approx discharge time : 50s
- Working temperature range : +5℃ -+60℃
- Extinguish agent : water
- Working pressure : 12Bar at 20 ℃
- Test pressure : 27bar
- Burst pressure : ≥55Bar
- Manufactured & Certified to : BS EN 3 -7: 2004 + A1: 2007, BS EN 3 -8: 2021 and
BS EN 3 -10: 2009
- Approx full weight : 14.50kg
- Approval : MED



PORTABLE 6L WATER FIRE EXTINGUISHER

- Model: HY -W6C
- Capacity : 6L
- CO2 Gas cartridge : 55g
- Cylinder diameter : 162mm
- Overall height : 505mm
- Type : Cartridge operated type
- Fire rating : 13A
- Approx discharge time : 30s
- Working temperature range : -+5℃ -+60℃
- Extinguish agent : water
- Working pressure : 12Bar at 20 ℃
- Test pressure : 27bar
- Burst pressure : ≥55Bar
- Manufactured&Certified to : BS EN 3 -7: 2004 + A1: 2007, BS EN 3 -8: 2021 and
BS EN 3 -10: 2009
- Approx full weight : 10.450kg
- Approval : MED



PORTABLE 5KG CO₂ FIRE EXTINGUISHER

- Type : WN/M5
- Extinguisher agent: CO₂
- Capacity : 5KG
- Cylinder volume:7.5L
- Cylinder height: 655mm
- Extinguisher weight:14.8KG
- Temperature range : -300C ~+600C
- Work pressure : 169.3bar
- Hydrotest pressure : 250bar
- Cylinder material : 34CrMo4
- Fire class : 89B
- Certificate: DNV GL MED



PORTABLE 2KG DRY POWDER FIRE EXTINGUISHER

- Model: HY -P2
- Capacity : 2kg
- Cylinder diameter : 110mm
- Overall height : 385mm
- Type : Pressure storage type
- Fire rating : 13A 70B C
- Approx discharge time : 12s
- Working temperature range : -30° -+60°
- Extinguish agent : ABC Dry powder
- Working pressure : 14Bar at 20 °
- Test pressure : 27bar
- Burst pressure : ≥55Bar
- Manufactured&Certified to : BS EN 3 -7: 2004 + A1: 2007, BS EN 3 -8: 2021 and
- BS EN 3 -10: 2009
- Approx full weight : 3.5kg
- Approval : MED



PORTABLE 6KG DRY POWDER FIRE EXTINGUISHER

- Brand : HWAYAN - F-POWER
- Model: HY -P6
- Capacity : 6kg
- Cylinder diameter : 150mm
- Overall height : 530mm
- Type : Pressure storage type
- Fire rating : 43A 233B C
- Approx discharge time : 17s
- Working temperature range : -30℃ -+60℃
- Extinguish agent : ABC Dry powder
- Working pressure : 14Bar at 20 ℃
- Test pressure : 27bar
- Burst pressure : ≥55Bar
- Approx full weight : 9.0kg
- Approval : MED



WHEELED 50KG DRY POWDER FIRE EXTINGUISHER

- Model: HY -P50
- Capacity : 50kg
- Cylinder diameter : 300mm
- Overall height : 1160mm
- Width : 450mm
- Depth : 500 mm
- Type : Pressure storage type
- Fire rating : A , B
- Approx discharge time : 95s
- Working temperature range : -30℃ -+60℃
- Extinguish agent : ABC Dry powder
- Working pressure : 14Bar at 20 ℃
- Test pressure : 27bar
- Burst pressure : ≥55Bar
- Manufactured&Certified to : EN 1866 -1 : 2007 ; EN 1866 -2:2014
- Approx full weight :
- Approval : MED

